

10042 NICHELINO (TO) – Via Novalesa, 9/11 . tel +39 011 35 80 966 r.a. – fax +39 011 35 82 750  
 Sede Legale: Via Bligny, 5 – 10122 Torino – Capitale Sociale 500.000,00 Euro I.V.  
 C.F. e P. IVA IT 04504770019 – REA TO 638304 – M. TO 027184  
[www.utemac.it](http://www.utemac.it) – email: [utemac@tin.it](mailto:utemac@tin.it)



### RADIAL DRILL

<b>Construction :</b> <b>Model :</b>	<b>SASS</b> <b>TRM 1900-2200</b> <b>Cod. 472.480.09</b>
Maximum drilling diameter from solid cast iron 20-22	100 mm
Maximum drilling diameter from solid steel R=60	80 mm
Sliding quill spindle diameter:	102 mm
Spindle morse taper:	6
Rotation speed:	32
Spindle speed values with 50 Hz motor – rpm/1'	18 ÷ 1600
Automatic feeds:	9
Maximum reach from column edge to spindle axis:	1900 mm
Minimum and maximum drilling radius:	660 ÷ 2505 mm
Vertical movement of the arm:	1040 mm
Column diameter:	550 mm
Spindle motor:	11 HP
Weight:	8000 kg

\* Technical data provided are not to be considered binding